



**GARD LT4**


**QUALITY AT  
THE BEST VALUE**

**FOR PASSAGES UP TO 4 M**

**CAME** 

[CAME.COM](https://www.came.com)





**PASSAGE WIDTH CLEARANCE**  
from **2.5 to 4 meters**

**MCBF**  
**1,5 million cycles**

Tested for intensive use up to  
**300 CYCLES/hour.**



## GARD LT4 FEATURES

### RELIABLE

thanks to the 24 V DC motor with ENCODER and ADVANCED SPEED CONTROL for monitoring the forces applied to the boom.

### FAST AND EFFICIENT

with maximum speed from 2 to 4 seconds depending on the length of the boom

### ADVANCED ELECTRONIC

developed with CONNECT technology and MODBUS protocol.

### SLIM AND ESSENTIAL BOOM


with availability of additional reflector stickers.

### SAFE

Compliant with EN 12453, it can easily pass the impact tests.

### CUSTOMIZABLE FINISH

Galvanized and painted steel Cabinet (RAL 2004) as standard, also available in AISI 304 stainless steel or any other RAL colour on request.



## ZL392-C CONTROL BOARD

The control board is placed directly under the upper cabinet cover. All the configuration and maintenance phases can therefore be carried out comfortably standing upright, with the cabinet closed, in total safety. The advanced control board of Gard LT4 is protected by an ABS cover, and includes:

- Command inputs and inputs for safety accessories configurable both as N.C. contacts and resistive contacts (8k2).
- Output for accessories and LED strip.
- Connector for fixed code radio receiver and rolling code up to 250 users (AF435/AF868).
- Terminals for external keyboard or RFID reader (R800/R700).
- CAME KEY slot for smart configuration from smartphone.
- MEMORY ROLL for saving the configurations.
- Serial ports for CONNECT technology, for combined/interlocked barriers or Modbus protocol integration.

## BATTERY-POWERED EMERGENCY SYSTEM

In the occurrence of a blackout or in any emergency situation where an electrical problem occurs, Gard LT4 is able to operate in complete safety thanks to an auxiliary battery power supply system (optional).

During normal operation with mains power supply, the system keeps the batteries fully charged in order to guarantee maximum reliability as soon as an emergency occurs.




# BARRIER ACCESSORIES



**001G0401**  
White painted aluminum boom with end cap. Section 60 x 40 mm, boom length: 4.2 m.




**001G0403**  
Red rubber shockproof edge with end caps.



**803XA-0580**  
White LED strips for booms up to 4-m long.



**001G0461**  
Package of 24 red, reflective, adhesive strips.



**803XA-0340**  
Painted aluminum skirt. 1720 mm module complete with junction brackets.



**001G0402**  
Tubular section boom made of white, painted aluminum. Ø 60 mm, boom length: 4.2 m.



**803XA-0590**  
Fastening flange for 001G0402.



**803XA-0440**  
Swing rest - skirt support bracket.



**803XA-0630**  
Heating system for operators installed in cold areas.



**803XA-0300**  
Auxiliary contacts unit for detecting the boom position.



**803XA-0330**  
Swing rest.



**001G02807**  
Fixed rest.




**806LA-0060**  
Flashing lights.



**803XA-0290**  
Control card kit for operating during power outages and for recharging batteries, with battery housing.



Intermediate plate



## EASY START-UP

Boom can be installed right or lefthand. Thanks to a dedicated intermediate plate, GARD LT4 allows installer to easily change the opening direction even after having installed the barrier, with no need for disassembling any component.


### Start it up in only three steps!

- 1 - Choose the opening direction
- 2 - Choose the boom length
- 3 - Run the first calibration

# CONNECT

CONNECT is the CAME technology that makes it possible to manage automations capable of improving the quality of life. Automations connected via the Internet offer added value to the user and open up new horizons for the installer's business.

CAME has chosen to develop in-house the technologies required to manage data flow and protection. No external agency processes the information, no server is located in remote locations around the world. An innovative technological heart that guarantees reliability and high security. CAME has invested in research and development with the aim of simplifying the installer's work, improving user experience and offering new digital services.




## CONNECT AT THE INSTALLER'S AND ADMINISTRATOR'S SERVICE

Connected automations can be managed remotely via PC or smartphone.  
The CONNECT platform enables automatic programming of transmitters, management of customers and systems installed, and monitoring of device status and scheduled maintenance.  
CONNECT allows the installer to offer a complete 24/7 service becoming the trusted partner for his customer.


## CONNECT AT THE CUSTOMER'S SERVICE

Through the free Apps that can be installed on any Android or iOS smartphone, the user can control the devices remotely.  
Compatible with Amazon Alexa devices, CAME automations can also be controlled by voice command.

## CONNECT MEANS



## DIMENSIONS (mm)



LM = Max. net clearance width 4 m

## THE COMPLETE RANGE

CODE	230 V AC barriers with encoder and 24 V DC operator and built-in control panel
803BB-0370	GLT40AOS - Automatic barrier with irreversible 24 V DC operator with encoder; galvanized steel and painted cabinet with set up for fitting accessories. Balancing spring included. Power supply 220 - 230 V AC.
803BB-0380	GLT40ROS - Automatic barrier with irreversible 24 V DC operator with encoder; galvanized steel and painted cabinet with set up for fitting accessories. Balancing spring included. Power supply 120 V AC.
803BB-0390	GLT40ACS - Automatic barrier with irreversible 24 V DC operator with encoder; galvanized steel cabinet with customized RAL painting and set up for fitting accessories. Balancing spring included. Power supply 220 - 230 V AC.
803BB-0400	GLT40AX4 - Automatic barrier with irreversible 24 V DC operator with encoder; AISI 304 satin-finish steel cabinet with set up for fitting accessories. Balancing spring included. Power supply 220 - 230 V AC.

## OPERATIONAL LIMITS

MODELS	803BB-0370	803BB-0380	803BB-0390	803BB-0400
Max. net clearance width (m)	4	4	4	4

● 24 V DC

## TECHNICAL CHARACTERISTICS

MODELS	803BB-0370	803BB-0380	803BB-0390	803BB-0400
Protection rating (IP)	54	54	54	54
Power supply (V - 50/60 Hz)	220 - 230 AC	120 AC	220 - 230 AC	220 - 230 AC
Power supply to motor (V)	24 DC	24 DC	24 DC	24 DC
Power (W)	190	190	190	190
Opening time at 90° (s)	2 ÷ 6	2 ÷ 6	2 ÷ 6	2 ÷ 6
Cycles/Hour	300	300	300	300
Operating temperature (°C)	-20 ÷ +55 (-40 with art. 803XA-0630)	-20 ÷ +55 (-40 with art. 803XA-0630)	-20 ÷ +55 (-40 with art. 803XA-0630)	-20 ÷ +55 (-40 with art. 803XA-0630)
RAL color	2004	2004	CUSTOMIZED	SATIN-FINISH

● 24 V DC

© CAME SPA - KADENUEE22 - 2022 - EN  
CAME reserves the right to make any changes to this document at any time. Even partial reproduction is prohibited.

# CAME

**CAME S.P.A.**  
Via Martiri della Libertà, 15  
31030 Dosson di Casier  
Treviso - ITALY

We are a leading multinational supplier of integrated high-tech solutions for automating residential, public and urban settings, which generate intelligent spaces for the wellbeing of people.

- GATE AUTOMATIONS
- VIDEO DOOR ENTRY SYSTEMS
- AUTOMATIONS FOR GARAGES AND INDUSTRIAL DOORS
- AUTOMATIC BARRIERS
- PARKING SYSTEMS
- TURNSTILES AND SPEED GATES
- BOLLARDS AND ROAD BLOCKERS
- TEMPERATURE CONTROL DEVICES
- AUTOMATIC DOORS
- SOLUTIONS FOR AWNINGS AND BLINDS
- BURGLAR ALARM SYSTEMS
- HOME AUTOMATION SYSTEMS

CE

